

## IRRIGATION PROBE FOR ABLATION DURING OPEN HEART SURGERY

### CROSS-REFERENCE TO RELATED APPLICATION

5           This application is a continuation-in-part of U.S. Application No. 09/370,601, filed August 10, 1999, the disclosure of which is incorporated herein by reference.

### FIELD OF THE INVENTION

10           The present invention is directed to an irrigation ablation probe for use during open heart surgery.

### BACKGROUND OF THE INVENTION

15           Atrial fibrillation is a common sustained cardiac arrhythmia and a major cause of stroke. This condition is perpetuated by reentrant wavelets propagating in an abnormal atrial-tissue substrate. Various approaches have been developed to interrupt wavelets, including surgical or catheter-mediated atriotomy. It is believed that to treat atrial fibrillation by radio-frequency ablation using a catheter, continuous linear lesions must be formed to segment the heart tissue. By segmenting the heart tissue, no electrical activity can be transmitted from one segment to another. Preferably, the segments are made too small to be able to sustain the fibrillatory process.

20           It has been found that over 60% of patients with mitral valve problems also have atrial fibrillation. Moreover, patients undergoing open heart surgery commonly develop atrial fibrillation during the surgery, and thus it would be useful to address this problem during the surgery. Accordingly, under certain circumstances it may be desirable to treat atrial fibrillation during open heart surgery, for example, when a patient is undergoing a mitral valve replacement or repair  
25           procedure. Accordingly, a need exists for devices and methods for treating atrial fibrillation during open heart surgery.

## SUMMARY OF THE INVENTION

The present invention is directed to an irrigation probe particularly useful for treating atrial fibrillation during open heart surgery. The probe of the present invention is also useful for other ablation and mapping procedures, particularly where irrigation of the ablation site is desired, such as for treating ventricular tachycardia. The invention is also directed to novel methods for treating atrial fibrillation with the probe of the invention. In accordance with the present invention, the probe comprises a rigid probe body and an irrigation electrode, which provides cooling and irrigation in the region of the tissue being ablated.

In one embodiment, the invention is directed to an irrigation ablation probe comprising a generally rigid probe body having proximal and distal ends. The probe body has an electrode at its distal end defining an inner cavity and having at least one irrigation opening through which fluid can pass and means for introducing fluid into the inner cavity. In a preferred embodiment an infusion tube having proximal and distal ends is in fluid communication with the inner cavity. In another preferred embodiment the infusion tube extends through the probe body for introducing fluid into the inner cavity of the electrode. In yet another preferred embodiment the electrode comprises an elongated body having first and second ends, which is fixedly attached, either directly or indirectly, to the distal end of the rigid probe body at a point along the elongated electrode body between its ends, wherein the angle formed between the distal end of the probe body and the electrode is greater than  $0^\circ$ . In still another preferred embodiment the electrode is attached generally perpendicular to the distal end of the rigid probe body and has at least three irrigation openings through which fluid can pass. In still yet another preferred embodiment the electrode comprises a flexible metal ribbon coiled around the outside of a looped irrigation tube fixedly attached, either directly or indirectly, to the distal end of the rigid probe body, where the irrigation tube has irrigation openings through which fluid can pass to the electrode and wherein the spaces between the coils provide openings through which fluid can pass to the outside of the irrigation probe.

In another embodiment, the invention is directed to an irrigation ablation probe. The probe comprises a generally rigid probe body as described above and a handle. The handle is mounted to the proximal end of the probe body. In a preferred embodiment, the generally rigid probe body

comprises a tubular body, an elongated electrode having first and second ends mounted to the distal end of the rigid probe body at a point along the elongated electrode body between its ends, wherein the angle formed between the distal end of the probe body and the electrode is greater than  $0^\circ$ , and a non-conductive sheath covering the length of the probe body. In still yet another embodiment the electrode comprises a flexible metal ribbon coiled around the outside of a looped irrigation tube fixedly attached either directly or indirectly to the distal end of the rigid probe body, where the irrigation tube has irrigation openings through which fluid can pass to the electrode and wherein the space between the coils provide openings through which fluid can pass to the outside of the irrigation probe.

In another preferred embodiment, the generally rigid probe body comprises tubing having proximal and distal ends and at least one lumen extending therethrough. An electrode as described above is mounted at the distal end of the tubing. The electrode has at least one irrigation opening through which fluid can pass. The probe body further comprises means for introducing fluid through the irrigation opening(s) of the electrode and a stiffening wire extending through a lumen of the tubing. A preferred means for introducing fluid comprises an infusion tube that extends through a lumen of the tubing with the distal end of the infusion tube in fluid communication with the one irrigation opening(s) in the electrode. In one embodiment, an elongated electrode having first and second ends is mounted to the distal end of the rigid probe body at a point along the elongated electrode body between its ends, wherein the angle formed between the distal end of the probe body and the electrode is greater than  $0^\circ$ . In a preferred embodiment the electrode is fixedly attached, either directly or indirectly, generally perpendicular to the rigid probe body and has at least three irrigation openings through which fluid can pass. In another preferred embodiment, the electrode comprises a flexible metal ribbon coiled around the outside of a looped irrigation tube fixedly attached either directly or indirectly to the distal end of the rigid probe body, where the irrigation tube has irrigation openings through which fluid can pass to the electrode and wherein the space between the coils provide openings through which fluid can pass to the outside of the irrigation probe.

In still another embodiment, the invention is directed to a method for treating atrial fibrillation in a patient. The method comprises opening the heart of the patient and ablating at least one linear lesion in the heart tissue using an irrigation probe as described above.

## 5 DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the present invention will be better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 is a side view of an embodiment of an irrigation probe according to the invention.

FIG. 2 is a side cross-sectional view of the handle of the irrigation probe of FIG. 1.

FIG. 3 is a perspective view of the distal end of the T-shaped irrigation probe of FIG. 1.

FIG. 4 is a side view of an alternative embodiment of an irrigation probe according to the invention.

FIG. 5 is a side cross-sectional schematic view of the distal end of the flexible metal ribbon irrigation probe of FIG. 4, wherein the rigid probe body comprises at least one lumen.

FIG. 6 is an end cross-sectional view of the distal end of the flexible metal ribbon irrigation probe of FIG. 4.

FIG. 7 is a side view of an alternative embodiment of an irrigation probe according to the invention.

FIG. 8 is a perspective view of the distal end of the flexible metal ribbon irrigation probe of FIG. 7.

## DETAILED DESCRIPTION

The present invention is directed to an irrigation probe for use during open heart surgery. In one embodiment, as shown in FIGs. 1 and 2, the irrigation probe **10** comprises a probe body **12** mounted to a handle **14**. The probe body **12** comprises a tubular body **16**, having proximal and distal ends, covered over by a non-conductive covering or sheath **18** along its length and an electrode **19** mounted at the distal end of the tubular body. The electrode **19** is a generally hollow tubular

structure having two ends **20** and defining an inner cavity therein. The electrode **19** is generally perpendicular to the tubular body **16** and fixedly attached to the tubular body **16** at a point between the two ends **20** of the electrode. The junction of the tubular body **16** and the electrode **19** forms an angle  $\alpha$  that is greater than  $0^\circ$ , preferably greater than  $10^\circ$ , more preferably greater than  $20^\circ$ , even more preferably ranging from  $70$  to  $110^\circ$ , still more preferably ranging from  $85$  to  $95^\circ$ . Still more preferably the electrode is fixedly attached at an angle  $\alpha$  of about  $90^\circ$  relative to the distal end of the probe body, thus forming a generally T-shaped arrangement. The tubular body **16** extends the entire length of the probe body **12**, with the proximal end of the tubular body extending into the handle **14** as described in more detail below. The probe body **12** preferably has a length (from the distal end of the handle to the distal end of the probe body) ranging from about 3.5 inches to about 12 inches, more preferably from about 5 to about 10 inches, still more preferably from about 7 to about 8 inches.

The tubular body **16** and the electrode **19** are both made of a material that is generally rigid so that the probe body **12** cannot bend during ablation, such as, for example, stainless steel (preferably 304VSS) or nitinol. Preferably the tubular body **16** and the electrode **19** have an inner diameter ranging from about 0.40 inch to about 0.80 inch, more preferably about 0.047 inch, and an outer diameter ranging from about 0.50 inch to about 0.90 inch, more preferably about 0.059 inch. If desired, the tubular body **16** and/or the electrode **19** can be heat-treated so that they are malleable enough to be bent by a physician to a desired shape but still rigid enough that they will not bend in use during a procedure. For example, for 304VSS stainless steel, the material is heated to about  $800^\circ\text{F}$  with electrical current or in a salt bath. The hollow interior of the tubular body **16** forms a lumen through which saline and the like may be conducted to the inner cavity of the electrode **19** and from there infused during a procedure, as described in more detail below. Alternatively the tubular body **16** could be solid and fluids could be introduced into the inner cavity of the electrode **19** by a separate external tube or the like.

The non-conductive sheath **18** extends from a proximal end inside the handle **14** to a distal end at the union of the tubular body **16** and the electrode **19**. The sheath **18** can be made of any suitable biocompatible non-conductive material, such as polyurethane. In this arrangement, the

electrode 19 is exposed, i.e., not covered by the sheath 18, for ablating tissue, mapping, etc. Preferably the length of the electrode 19 ranges from about 0.50 inch to about 1.5 inches, more preferably from about 0.75 inch to about 1.25 inches.

In the depicted embodiment, the length of the probe body 12 is approximately 7 inches. The proximal section of the probe body 12, i.e., the portion extending from the handle 14, is approximately 5.5 inches. The length of the electrode 19, is approximately 1 inch.

As shown in detail in FIG. 3, the electrode 19 has a series of irrigation openings 21 for passage of a cooling fluid out through the inner cavity of the electrode 19. The irrigation openings 21 can take any suitable shape, such as rectangular or oval slots or round holes. In a preferred embodiment the electrode 19 has at least three irrigation openings 21. The irrigation openings 21 are preferably in the section of the electrode 19 that is to be in contact with the tissue during a procedure, e.g., to enhance the cooling of an ablation site.

Saline or other suitable fluid is introduced into the inner cavity of the electrode 19 through any suitable means. In the embodiment of FIGs. 1 to 3, fluids are introduced into the inner cavity of the electrode 19 via the tubular body 16 through a luer hub 22 or the like at the proximal end of the probe 10. The luer hub 22 is connected to a flexible plastic tubing 24, e.g., made of polyimide. The plastic tubing 24 is attached, either directly or indirectly, to the proximal end of the tubular body 16, preferably within the handle 14, as shown in FIG. 2. Alternatively, the tubing 24 can be connected to a suction source (not shown) to permit aspiration of fluid from the region of tissue being operated on.

As shown in FIG. 2, the handle 14 comprises a housing 26 having a generally open interior 28. The tubular body 16 and sheath 18 extend into the distal end of the handle housing 26. In the depicted embodiment, the sheath 18 terminates a short distance proximal to the distal end of the housing 26. The tubular body 16 continues proximally beyond the sheath 18. The flexible plastic tubing 24 extends into the proximal end of the handle housing 26. The plastic tubing 24 is attached to the tubular body 16 within the open interior 28 of the handle, preferably at a point proximal to the proximal end of the sheath 18. The plastic tubing 24 can be attached to the tubular

body 16 by any suitable means, for example, polyurethane glue. By this design, cooling fluid is introduced through the luer hub 22, through the plastic tubing 24, through the tubular body 16 and out the irrigation openings 21 in the electrode 19.

Alternatively, fluid could be supplied to the electrode 19 and thereby the irrigation openings 21 via a separate irrigation tube (not shown) that can either run external to the tubular body 16 and attach directly to the electrode 19, or can extend through the tubular body 16 to the electrode 19. In either, case this separate irrigation tube could be made of any suitable material, e.g., plastic or metal, and attach to the electrode 19 by any direct or indirect means.

An electrode lead wire 30 having proximal and distal ends is electrically connected at or adjacent its distal end to the probe body 16. The proximal end of the lead wire 30 is attached to a connector 32 for connection to a suitable source of ablation energy, e.g., radio frequency energy, or to an appropriate monitor. In the depicted embodiment, the lead wire 30 extends into the proximal end of the handle housing 26. Within the open interior 28 of the handle 14, the distal end of the lead wire 30 is wrapped around the portion of the tubular body 16 not covered by the sheath 18 and held in place by solder or the like. The portion of the lead wire 30 that extends outside the handle 14 is covered by a flexible plastic protective tubing 34, e.g., made of polyimide.

An alternative embodiment of an irrigation probe according to the invention is shown in FIGs. 4 to 6. As shown in FIG. 4, the probe 10 comprises a probe body 12 and a handle 14. The probe body 12 comprises a non-conductive tubing 40 having proximal and distal ends. In a particularly preferred embodiment, the non-conductive tubing 40 comprises outer and inner plastic walls, e.g., of polyurethane or polyimide, surrounding an imbedded braided mesh of stainless steel or the like. Preferably the tubing has an outer diameter of less than 8 French, more preferably less than 7 French. The tubing 40 has three lumens 42, 44 and 46 extending along its length.

131 The irrigation probe comprises a metal ribbon electrode 47 at the distal end 48 of the non-conducting tube 40 comprising an exposed metallic ribbon 49 that is coiled around a loop of irrigation tubing 56, both of which are indirectly or directly fixedly attached to the distal end 48 of the non-conducting tube 40. As illustrated in FIG. 5, the probe's distal end 48 is generally solid,

having a fluid passage 50 and first and second blind holes 52 and 54 that correspond in size and location to the three lumens 46, 42 and 44, respectively, in the non-conductive tubing 40. In the embodiment shown, the fluid passage 50 is in fluid communication with the inner cavity of the flexible irrigation tube 56, which extends from the distal end of the fluid carrying lumen 46 out of the probe's distal end 48. The irrigation tube 56 has a series of irrigation openings 57 for passage of a cooling fluid out through the spaces between the coils of the metallic ribbon 49, as described in more detail below. The irrigation openings 57 can take any suitable shape, such as rectangular or oval slots or round holes. In a preferred embodiment the irrigation tubing 56 has at least three irrigation openings 57. The irrigation openings 57 are preferably in the section of the irrigation tubing 56 corresponding to the section of the metal ribbon electrode 47 that is to be in contact with the tissue during an ablation procedure to enhance the cooling of the ablation site.

The metallic ribbon 49 is coiled loosely around the irrigation tube 56 such that fluid can pass unimpeded to the outside of the metal ribbon electrode 47. The metal ribbon electrode 47, as shown in detail in FIG. 5, comprises a continuous ribbon 49 of conducting metal, extending outside of the probe's distal end 48 and coiled about the flexible irrigation tube 56 in a loop, having a radius ranging from about 0.5 inch to 1.5 inches. The metal ribbon 49 can be coiled in any manner wherein the coils of the metal ribbon define an inner tubular passage through which the irrigation tube 56 runs and wherein the coils of metal ribbon 49 are generally spaced sufficiently far apart to allow fluid to escape through the irrigation passages. In a preferred embodiment the metal ribbon electrode 49 is coiled around from 1% to 100% of the length of the irrigation tube 56 that is outside the probe body 12. More preferably, the metal ribbon 49 is coiled around from 20% to 80% of the length of the irrigation tube 56, still more preferably the metal ribbon electrode is coiled around from 40% to 60% of the length of the irrigation tube 56. The metal ribbon 49 can be made of any suitable material, and is preferably machined from a .005 inch thick ribbon of nitinol.

The metal ribbon 49 and the irrigation tube 56 can be attached to the probe's distal end 48 in any suitable manner. In the depicted embodiment, the metal ribbon 49 and the irrigation tube 56 are each attached at both ends to the probe's distal end 48 by a polyurethane glue seal 58 or the like.



However, any other means for fixedly mounting the metal ribbon 49 and the irrigation tube 56 on the probe's distal end 48 can also be used. For example, only one end of the metal ribbon 49 and/or the irrigation tube 56 may be attached to the probe's distal end 48.

The metal ribbon electrode 47 is connected to a lead wire 67 having proximal and distal ends. The proximal end of the lead wire 67 for the metal ribbon electrode 47 extends through the third lumen 46 of tubing 40 and through the handle 14. The distal end of the lead wire 67 for the metal ribbon electrode 47 extends through the third lumen 46 and is attached to the metal ribbon electrode 47 by any conventional technique, for example, by soldering.

In the embodiment shown, a mapping ring electrode 62 is mounted on the tubing 40 proximal to the probe's distal end 48. It is understood that the presence and number of ring electrodes may vary as desired. The ring electrode 62 is slid over the tubing 40 and fixed in place by glue or the like. The ring electrode 62 can be made of any suitable material, and is preferably machined from platinum-iridium bar (90% platinum/10% iridium).

The ring electrode 62 is connected to a lead wire 64 having proximal and distal ends. The proximal end of the lead wire 64 for the ring electrode 62 extends through the first lumen 42 of tubing 40 and through the handle 14. The lead wire 64 can be connected to the ring electrode 62 by any conventional technique. Connection of the lead wire 64 to the ring electrode 62 is preferably accomplished by first making a small hole through the tubing 40. Such a hole can be created, for example, by inserting a needle through the tubing 40 and heating the needle sufficiently to form a permanent hole. The lead wire 64 is then drawn through the hole by using a microhook or the like. The ends of the ring electrode lead wire 64 are then stripped of any coating and soldered or welded to the underside of the ring electrode 62, which is then slid into position over the hole and fixed in place with polyurethane glue or the like. Any other means for fixedly mounting the ring electrode 62 to the tubing 40 can also be used.

Both lead wires 64 and 67 terminate at their proximal end in a connector 32 that may be plugged into an appropriate monitor and/or source of radio frequency or other ablation energy. The portion of the lead wires 64 and 67 extending out the proximal end of the handle 14 are enclosed

within a protective tubing 34, which can be made of any suitable material, preferably polyimide, as shown in FIG. 4.

An infusion tube 72 is provided for infusing fluids, e.g., saline, to cool the metal ribbon electrode 47 during ablation. The infusion tube 72 may also be used to infuse drugs to the ablation site. The infusion tube 72 may be made of any suitable material, and is preferably made of polyimide tubing. The infusion tube 72 has proximal and distal ends, with its distal end mounted in the fluid passage 50 of the probe's distal end 48 by any suitable method, e.g., by polyurethane glue or the like. The infusion tube 72 extends from the probe's distal end 48, through the third lumen 46 of the tubing 40, and through the handle 14. As would be recognized by one skilled in the art, the distal end of the infusion tube 72 can be positioned at any point within the third lumen 46. The proximal end of the infusion tube 72 ends in a luer hub 22 or the like. Any other means for infusing fluids to the metal ribbon electrode 47 can also be used, including running the infusion tube 72 external to the tubing 40 and fluid passage 50.

A stiffening wire 74, having proximal and distal ends, is mounted in the second lumen 44 of the tubing 40. The stiffening wire 74 is made of a rigid metal or plastic material, preferably stainless steel, to prevent the probe body 12 from bending during a procedure. If desired, the stiffening wire 74 can be heat-treated so that it is malleable and can be bent to a desired shape before use, but still rigid enough that it will not bend in use during a procedure. A non-conductive tube 76, preferably made of polyimide, is attached to the distal end of the stiffening wire 74 for mounting the stiffening wire in the probe's distal end 48. The non-conductive tube 76 extends out of the second lumen 44 and into the second blind hole 54 in the probe's distal end 48, and is secured in place by polyurethane glue or the like. Any other means for securing the stiffening wire 74 within the probe can also be used. The proximal end of the stiffening wire 74 terminates in the handle 14 or near the proximal end of the probe body 12.

While FIGs. 4 to 6 depict an irrigation probe 10 having a metal ribbon electrode 47, it will be understood that the irrigation probe 10 described above and illustrated in FIGs. 4 to 6 could also house the generally T-shaped electrode 19 illustrated in FIGs. 1 to 3. In this embodiment the

generally T-shaped electrode **19** is fixedly attached, either directly or indirectly, to the probe's distal end **48** such that the fluid passage **50** is in fluid communication with the inner cavity of the generally T-shaped electrode **19**. The construction and function of the lumens **42**, **44**, and **46**, and the remainder of the probe **10** would be similar to that described above and shown in FIGs. 4 to 6.

5 In another embodiment, as shown in FIGs. 7 and 8, the irrigation probe **10** comprises a probe body **12** mounted to a handle **14**, which is described in detail above. The probe body **12** comprises a tubular body **16**, having proximal and distal ends, covered over by a non-conductive covering or sheath **18**. In this embodiment, a metal ribbon electrode **35** comprising a coiled metal ribbon **33** and a loop of flexible irrigation tube **36** is disposed at the distal end of the probe body **12** and fixedly  
10 attached, either directly or indirectly, to the distal end of the tubular body **16**. The probe body **12** preferably has a length (from the distal end of the handle to the distal end of the probe body) ranging from about 3.5 inches to about 12 inches, more preferably from about 5 to about 10 inches, still more preferably from about 7 to about 8 inches.

The tubular body **16** is made of a material that is generally rigid so that the probe body **12**  
15 cannot bend during ablation, such as, for example, stainless steel (preferably 304VSS) or nitinol. Preferably the tubular body **16** has an inner diameter ranging from about 0.40 inch to about 0.80 inch, more preferably about 0.047 inch, and an outer diameter ranging from about 0.50 inch to about 0.90 inch, more preferably about 0.059 inch. If desired, the tubular body **16** can be heat-treated so that it is malleable enough to be bent by a physician to a desired shape but still rigid enough that it will  
20 not bend in use during an ablation procedure. The hollow interior of the tubular body **16** forms a lumen through which saline and the like may be conducted to the irrigation tube **36** of the metal ribbon electrode **35** and from there infused during an ablation procedure, as described in more detail below. Alternatively, the tubular body **16** could be solid, in which case fluids could be introduced into the irrigation tube **36** via a separate external tube or the like.

25 The non-conductive sheath **18** extends from the proximal end of the tubular body **16** inside the handle **14** to the distal end of the tubular body at the union of the tubular body **16** and the metal ribbon electrode **35**. The sheath **18** can be made of any suitable biocompatible non-conductive material, such as polyurethane. Preferably the diameter of the loop of the metal ribbon electrode **35**

ranges from about 0.50 inch to about 1.5 inches, more preferably from about 0.75 inch to about 1.25 inches.

In the depicted embodiment, the length of the probe body 12 is approximately 7 inches. The proximal section of the probe body 12, i.e., the portion extending from the handle 14, is approximately 5.5 inches. The diameter of the loop of the metal ribbon electrode 35 is approximately 1 inch.

As shown in detail in FIG.8, the metal ribbon electrode 35 comprises an irrigation tube 36 having first and second ends 37, at least one of which is fixedly attached either directly or indirectly to the tubular body 16, similar to the embodiment depicted in FIGs. 4 to 6. The irrigation tube 36 is bent so as to form a loop and the metal ribbon 33 is in turn coiled around the irrigation tube 36 and fixedly attached, either directly or indirectly, to the tubular body 16. In one preferred embodiment, the metal ribbon 33 and irrigation tube 36 are both attached to the tubular body 16 at both ends by any direct or indirect means, e.g., via a glue seal 38 as shown above in FIG. 5. Any other means for attaching the metal ribbon 33 and the irrigation tube 36 can also be used.

As shown, the irrigation tube 36 has a series of irrigation openings 39 for passage of a cooling fluid out through the metal ribbon 33. The irrigation openings 39 can take any suitable shape, such as rectangular or oval slots or round holes. In a preferred embodiment, shown in FIG. 8, the irrigation tube 36 has at least three irrigation openings 39. The irrigation openings 39 are preferably in the section of the irrigation tube 36 corresponding to the section of the metal ribbon 33 that is to be in contact with the tissue during a procedure, e.g., to enhance the cooling of the ablation site. The metal ribbon 33 is coiled loosely around the irrigation tube 36 such that fluid can pass unimpeded through the metal ribbon 33.

Saline or other suitable fluid is introduced into the tubular body 16 through a luer hub 22 or the like at the proximal end of the probe 10. The luer hub 22 is connected to a flexible plastic tubing 24, e.g., made of polyimide. The plastic tubing 24 is attached, either directly or indirectly, to the proximal end of the tubular body 16, preferably within the handle 14, as shown in FIG. 7. By this design, cooling fluid is introduced through the luer hub 22, through the plastic tubing 24, through the

tubular body 16, through the first and second ends 37 of the irrigation tube 36 and out the irrigation openings 39.

The irrigation probe shown in various embodiments in FIGs. 1 to 8, having either a metal ribbon electrode or a generally T-shaped electrode, can be used in any manner in which a standard probe can be used. For example, the above described probes can be used during open heart surgery for ablation. During an ablation procedure, the heart is opened and the irrigated electrode is used to form continuous linear lesions by ablation. As used herein, a linear lesion refers to any lesion, whether curved or straight, between two anatomical structures in the heart that is sufficient to block a wavelet, i.e., forms a boundary for the wavelet. Anatomical structures, referred to as "atrial trigger spots", are those regions in the heart having limited or no electrical conductivity and are described in Haissaguerre et al., "Spontaneous Initiation of Atrial Fibrillation by Ectopic Beats Originating in the Pulmonary Veins", New England Journal of Medicine, 339:659-666 (Sept. 3, 1998), the disclosure of which is incorporated herein by reference. The linear lesions typically have a length of from about 1 cm to about 4 cm, but can be longer or shorter as necessary for a particular procedure.

The probe described in FIGs 1 to 3 having a long tubular electrode is particularly useful for this procedure because it can create relatively long lesions. The probe depicted in FIGs. 4 to 6 above, having a smaller but flexible ablation electrode, is useful if the surgeon does not want to ablate as much tissue or wants to ablate a more precise lesion. The above-described probe having a flexible body is particularly useful if the surgeon needs to have a probe that conforms to a particular site to better ablate a desired region of tissue. Additionally, the flexible electrode is particularly useful for ablating locations where it is desirable to have the electrode conform to the tissue, rather than having the tissue conform to the electrode, for example, an atrial appendage. Further, the circular coil design can be used to form a generally circular region around an orifice of a tubular structure, such as a pulmonary vein, the coronary sinus, the superior vena cava, or the inferior vena cava. Once the heart is closed, the surgeon can use the probe on the outside of the heart, not only to ablate, but to verify that the electrical conduction has been stopped using the mapping electrodes. As would be

recognized by one skilled in the art, the probes of the present invention can be used during open heart surgery for other procedures as well.

5 The preceding description has been presented with reference to presently preferred embodiments of the invention. Workers skilled in the art and technology to which this invention pertains will appreciate that alterations and changes in the described structure may be practiced without meaningfully departing from the principal, spirit and scope of this invention.

Accordingly, the foregoing description should not be read as pertaining only to the precise structures described and illustrated in the accompanying drawings, but rather should be read consistent with and as support to the following claims which are to have their fullest and fair scope.

10

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2